

USF-105DDA-12GA Datasheet

1. Specifications

Basic specifications

Temperature	0 °C to 40 °C
Humidity	30% to 90% (no condensation)
Power	+12V DC (Supplied by USF frame)
Consumption	0.7 A
Dimensions	Front Module: 106 (W) x 357 (D) mm Rear Module: 114 (W) x 20.2 (H) mm
Weight	240 g
Required Slot	1 Slot

Technical specifications

Video Input	12G-SDI: 12Gbps 3G-SDI: 3Gbps HD-SDI: 1.5Gbps SD-SDI: 270Mbps DVB-ASI: 270Mbps 75Ω BNC x 1
Video Output	12G-SDI: 12Gbps 3G-SDI: 3Gbps HD-SDI: 1.5Gbps SD-SDI: 270Mbps DVB-ASI: 270Mbps 75Ω BNC x 5
Cable Compensation (Reference value)	Automatic Cable Compensation 12G-SDI: Max. 70m (L-5.5 CUHD-equivalent cable) 3G-SDI: Max. 100m (5C-FB-equivalent cable) HD-SDI: Max. 100m (5C-FB-equivalent cable) SD-SDI: Max. 200m (5C-2V-equivalent cable) * The above cable lengths vary depending on cable quality and usage conditions.
SNMP	Supports version v2c

Accessories

USB flash drive and Screws for rear module installation

2. External Dimensions

(All dimensions in mm.)

