

LED DISPLAYS

# Litepix® series





THE LED SCREEN OF CHOICE FOR RENTAL SPECIALISTS

www.alfalite.com

# FAST-LOCKS FOR RENTAL COMPANIES

- Top main lock and fast side lock (2 locks vs 4/6)
- Top removable positioners
- Retractable side positioner










# EASY AND FAST MAINTENANCE

- Front and rear maintenance
- No tools required
- Fast and accurate installation and dismantling
- MOM: Module replacement with unified calibration





Chassis handles can be used as a ladder



CURVE OPTION

# MODULAR AND VERSATILE DESIGN

- Neutrik connectors
- Concave/convex curve +/-15°
- Aluminium or Magnesium alloy Cabinets
- ORIM (Optical Resin Injection Module)





#### **PCB**

4/6 Layers

Gold surface treatment

Technical RoHS marking. UL Certification.





- Easy to clean with enhanced protection against hits and humidity
- Highest protection against static electricity. ESD>10KV

MODULAR

- <0,02 mm pinpoint accuracy/space between modules
- Fire resistance parameters. UL94-0 compliant







#### **SMART PANEL**

- Preemptive and remote maintenance
  - Temperature and humidity
  - Data/video connectors
  - Sending and receiving card control
- Remote monitoring and control
  - External elements
  - Color and brightness parameters Refresh rate (Hz)

DISPLAY CONFIGURATION REMOTE PANEL









#### **EUROPEAN MANUFACTURER 4.0**

- Mechanical and electronic industrial design
  - Design tools for CAD and 3D AR simulation (Augmented reality)
- PCB Manufacture. In-house SMD production lines
  - Traceability
  - Control system and automation
  - Measurements for BIG DATA
- LEAN Manufacturing methodology

Quality, Reliability, Durability



#### **SMART POWERBOX**

- Powerbox Status display -Status Report database collection, Data/video Main/Back-up signal state



No fans-Noise Free Wireless FA, HUB and modules Heat dissipation by free convection

#### ALFALITEWOW COLOR/BRIGHTNESS ALFALITE CUSTOMISED CALIBRATION





#### INSTALLATION ACCESSORIES

# STACK SYSTEM



# FLOOR APPLICATIONS



Polycarbonate Tempered Glass Interactive and you can step on it



#### HANGING BAR



#### TRANSPORTATION/SHIPPING



Flight cases by Alfalite The highest protection Lightweight

# CUTTING EDGE TECHNOLOGY, DESIGNED TO THRILL

# **PRODUCT SPECIFICATIONS**

	ALFALITE LITEPIX SERIES°							
	LITEPIX OUTDOOR SERIES			LITEPIX INDOOR SERIES				
MODEL	LITEPIX 3+	LITEPIX 4+	LITEPIX 5+	LITEPIX 1Pro	LITEPIX 1i	LITEPIX 2Pro	LITEPIX 2i	LITEPIX 3i
PIXEL PITCH (mm)	3.9	4.8	5.9	1.5	1.9	2.6	2.9	3.9
PANEL RESOLUTION (pixel)	128 x 128	104 x 104	84 x 84	320 x 320	256 x 256	192 x 192	168 x 168	128 x 128
MODULE RESOLUTION (pixel)	64 x 64	52 x 52	42 x 42	160 x 160	128 x 128	96 x 96	84 x 84	64 x 64
PANEL SIZE (mm)	500 x 500			500 x 500				
PIXEL CONFIGURATION	RGB 3 ON 1 SMD			RGB 3 ON 1 SMD				
MODULE SIZE (mm)	250 x 250			250 x 250				
PANEL WEIGHT (kg) Aluminium/Magnesium	8.9/7.8			8.9/7.8				
BRIGHTNESS (cd/m²)	5.000			1.900			1.500	
REFRESH RATE (Hz)	3.840			7.680			4.440	
IP PROTECTION LEVEL (rear/front)	IP65 outdoor			IP22 indoor				
AVERAGE POWER CONSUPTION (W/panel)	35			35				
LIFESPAN (hours)	100.000			100.000				
CURVE VERSION (2,5° Steps)	-15°/+15°			0° / 7.5°			-15°/+15°	



\* Technical specifications are flexible and can be modified in accordance with the project requirements.

\*\* EMC and RoHS certifications exceed the normal values.



P.I. Doña Paca. C/ Zalema, 2. 21720 Rociana del Condado Huelva. SPAIN.

Website: www.alfalite.com info@alfalite.com Telf. 959 41 73 71







