

MFR-3100EX Datasheet

1. Specifications

MFR-3100EX Basic specifications

Temperature / Humidity	0°C to 40°C / 30% to 85% (no condensation)
Power	100 V AC to 240 V AC \pm 10%, 50/60Hz IN x 2 (MFR-31PS required for redundant power configuration)
Consumption	100 V AC to 120 V AC: 671 VA (661 W), 220 V AC to 240 V AC: 608 VA (510 W)
Dimensions	430 (W) x 177 (H) x 400 (D) mm EIA 4RU 482 (W) (Including rack mount brackets)
Weight	25 kg (with full options)

MFR-3100EX Technical specifications

Video Formats	
UHD 4K (12G-SDI) (3G-SDI)	2160p / 59.94, 50 (MFR-8SDIGB / 8SDOGB required) Single Link 12G-SDI (SMPTE ST 2082-10) Quad Link 3G-SDI (SMPTE ST 425-5)
HD (3G-SDI)	1080p / 60, 59.94, 50 (SMPTE 424M)
HD (HD-SDI)	1080i / 60, 59.94, 50 1080p / 30, 29.97, 23.98, 25, 24 1080PsF / 30, 29.97, 23.98, 25, 24 720p / 60, 59.94, 50 (SMPTE 292M)
SD (SD-SDI)	525/59.94i, 625/50i (SMPTE 259M) (W/ MFR-8SDI/SDO)
DVB-ASI	Compliant to EN 50083-9 (W/ MFR-8SDI/SDO)
Matrix Size	Min. 8 x 8 to Max. 64 x 72 (Max. of logical matrix: 512 x 512) Number of input slots: 8 Number of output slots: 9 (Expandable on an 8-channel basis)
Video Input	
MFR-8SDI (as video input)	3G/HD/SD-SDI Input Card (Max. 8 cards) - 75-ohm BNC x 8 Cable Equalization 3G/HD-SDI: 100 m (5C-FB cable) SD-SDI: 200 m (5C-2V cable)
MFR-8SDIGB	12G/3G-SDI Input Card (Max. 8 cards) - 75-ohm BNC x 2 (12G-SDI or 3G-SDI) - 75-ohm BNC x 6 (3G-SDI) I/O delay selection - Delay (H) (0.3H-1H), 1 frame, 1 frame+ Delay (H) Cable Equalization - 12G-SDI: 100 m (L-5.5CUHD cable) - 3G/HD-SDI: 100 m (5C-FB cable) - SD-SDI: 200 m (5C-2V cable)

Video Output	
MFR-8SDO	3G/HD/SD-SDI Output Card (Max. 9 cards) - 75-ohm BNC x 8 (Auto reclocking)
MFR-8SDOGB	12G/3G-SDI Output Card (Max. 9 cards) - 75-ohm BNC x 2 (12G-SDI or 3G-SDI) - 75-ohm BNC x 6 (3G-SDI) I/O delay selection - Delay (H) (0.3H-1H), 1 frame, 1 frame+ Delay (H)
Audio Input	
MFR-8AAI	Analog Audio Input Card with A/D converter (Max. 8 cards) - 25-pin D-sub (female) x 2 (8 stereo pairs, 16 channels) - Balanced or unbalanced, 600-ohm or high impedance - A/D conversion: 48kHz / 24bit
MFR-8AESI	AES/EBU Audio Input Card (Max. 8 cards) - 75-ohm, BNC x 8 (8 stereo pairs, 16 channels) - 48kHz / 24bit (No limitation for MFR-8AESO)
MFR-8SDI (as audio input)	MADI Audio Input Card (Max. 8 cards) - 75-ohm, BNC x 8 (MADI x 8) - MADI: 64-channel, 48kHz / 24bit
Audio Output	
MFR-8AAO	Analog Audio Output Card with D/A converter (Max. 9 cards) - 25-pin D-sub (female) x 2 (8 stereo pairs, 16 channels), - Balanced or unbalanced, 600-ohm or 100-ohm - D/A conversion: 48kHz / 24bit
MFR-8AESO	AES/EBU Audio Output Card (Max. 9 cards) - 75-ohm BNC x 8 (8 stereo pairs, 16 channels) - 48kHz / 24bit (No limitation for MFR-8AESI)
MFR-8MADIPO	MADI/SDI Output Card (Max. 9 cards) - 75-ohm BNC x 8 (MADI/SDI x 8) Audio output - MADI: 64-channel, 48kHz / 24bit (AES10-2008 (MADI)) - Audio I/O delay: 1 ms or less Video output: - 3G-SDI: 1080/59.94p, 1080/50p - HD-SDI: 1080/59.94i, 1080/50i, 1080/29.97PsF, 1080/23.98PsF, 720/59.94p - Additional delay time: Delay (H) (0.2H-1H)
MFR-8AESPO	AES/EBU Audio Output Card (Max. 9 cards) - 75-ohm BNC x 8 (8 stereo pairs, 16 channels) - 48kHz / 24bit - Audio I/O delay: 1 ms or less
Multiviewer	
MFR-16MV	16 Split Output Card (Max. 4 cards) - 2 slots required per card - 75-ohm BNC x 16
Reference Input	BB: 0.429 Vp-p (NTSC)/0.45 Vp-p (PAL) or Tri-level Sync: 0.6 Vp-p 75-ohm BNC x 1, loop-through (Terminate with 75-ohm, if unused.)

Interfaces	
MFR-LAN	10/100BASE-TX RJ-45 x 2 (For connecting up to 128 RU/GPI units.) (Second LAN port used in redundant CPU configuration)
PC-LAN	10/100/1000BASE-T RJ-45 x 2 (for PC and external device connection) (Second LAN port used in redundant CPU configuration)
EXT-LAN	10/100/1000BASE-T RJ-45 x 4 (for PC and external device connection) (MFR-31VP required)
ALARM	9-pin D-sub (female) x 1 (Power alarm, Fan alarm, Crosspoint error, CPU changeover and Secondary CPU error)

Options

MFR-31CPU	Redundant CPU card
MFR-31PS	Redundant power supply unit (with AC cord and AC cord clamp.)

Other Options

MFR-18/39RUA MFR-40RU MFR-16RU/16RUD/16RUTA MFR-16/32/64RUW	Remote Control Unit
MFR-GPI	Interface Expansion Unit
MFR-TALM	Tally Manager Unit
MFR-RULINK *	Remote Control Relay Unit
MFR-31VP *	Video Process Card for MFR-3100EX
MFR-31VPS *	Software Option for MFR-31VP
MFR-CTSP *	Software Panel for MFR Series
MFR-8SDIFS *	FS Input Card for MFR-3100EX
MFR-8SDODL *	AVDL Output Card for MFR-3100EX

* Planned for future support

2. External Dimensions

(All dimensions in mm.)

